



PRODUCT DATA



600GL Coatings Remover (Formerly SOY•Gel™ Paint and Urethane Remover)

Franmar's most-asked-for product, **600GL**, continues to impress contractors with its ease of use and powerful removal properties. With three times the coverage rate of traditional petroleum removers, **600GL** effectively removes multiple layers of topical sealers, acrylics, enamels, urethanes, latex, some epoxies, and other single-component coatings. Made with soybeans, **600GL** is a safe, low-odor, non-caustic, green coating remover.

As a leading innovator in green cleaning products, Franmar Chemical, Inc. introduced **600GL** as a soy based paint remover, and changed the industry. **600GL** is 100% biodegradable, practically odorless, and is safe for your hands, your work, and your customers.

Coverage:

Coverage per square foot varies depending on type and age of coating, number of layers and method of application.

Horizontal: Average coverage is 125 sq ft per gallon (max 200 sq ft per gallon)

Vertical: Average coverage is 75 sq ft per gallon

Test Area:

Due to variances in surfaces and conditions, always test in a small, inconspicuous area before using on complete project.

Application:

Apply a thick layer of **600GL** by pouring, brushing, squeegee, or commercial airless sprayer. Applying too thin will cause **600GL** to dry out before removal is complete. Use a scraper to check if the coating is softened down to the surface. If not, wait longer and recheck. When the coating is completely softened, remove with a scraper.

Clean Up:

Use **BLUE BEAR 700DG Degreaser** or water and a scrub brush, mop, or power washer to clean remaining thin residue. Remove excess coating(s) and **600GL** before using a power washer for final cleaning. Allow surface to dry before further preparations.

Usage Tips from the Pros:

- For large application areas, use a professional airless sprayer or a 4-stage HVLP sprayer.
- For tough coatings or numerous layers, use a notched 1/2" squeegee or 1/4" gauge rake. Square footage will be greatly reduced.
- When used outdoors, cover with a 2mil or thicker plastic to help keep **600GL** wet and working.

Biodegradable: Meets or exceeds ASTM standards

Precautions: Concrete surfaces may darken with use of **600GL**. Protect plants and vegetation with a plastic drop cloth. Always use care to prevent overspray from getting on surfaces other than the one being prepped or cleaned.

Warnings: May cause skin irritation. May cause eye irritation. May cause respiratory irritation or may cause drowsiness and dizziness. May be harmful if swallowed. This product contains a chemical known to the state of California to cause birth defects or other reproductive harm. Keep out of reach of children.

Flash Point Above 200°F (93.3°C)

pH Level 8.1 pH of 1/10 wt/wt solution in soft water

VOC (Volatile Organic Compounds) 49%, 4.249 lb/g, 509 g/l
California and OTC Compliant

Ingredients: N-Methyl Pyrrolidone, Dibasic Ester LVP, Soy Ester, Proprietary Thickening and Surfactant Blend

Safe for Use On: Concrete, masonry, wood, and metal

Do Not Use On: PVC, drywall, limestone, plastic, veneer, terrazzo tile, or rubber

let's Clean
Pty Ltd

PO Box 36, Artarmon
Sydney, NSW 2064

Ph: 02 9451 822

www.lets-clean.com.au

CHEMICAL EMERGENCY:

Australia Toxic
Emergency Phone
Ph: 13 11 26

Rev. 1/22/2015