



Durability & Corrosion Resistance (R3 Rating)

All Builders Steel Direct Lintels and T-Bars are hot dip galvanized with a heavy zinc coating of 600 g/m² which complies with an R3 durability rating.

Durability is a function of the thickness of the zinc coating, R4 durability can be achieved when coated with a two part epoxy coating.

AUSTRALIAN STANDARDS

AS/NZS 4680:2006
 R3 AS/NZS 2699.3.2001
 AS 3700:2001
 AS 4100:1998
 AS 1594:1997
 AS 1170:1:1989+A1
 AS 1170:2:1989+A1+A2+A3

Standard Stock Lengths

Product	Section	Lengths						
		0.8	0.9	1.0	1.1	1.2		
Flat Bar	85mm x 7mm							
Angle	100mm x 100mm	0.9	1.2	1.5	1.8	2.1		
Angle	150mm x 100mm	2.1	2.4	2.7	3.0	3.3	3.6	4.0
Angle	150mm x 100mm x 10mm	3.2	5.8					
T-Bar	200mm (6) x 200mm (6)	1.2	1.3	1.4	1.5	1.6	1.8	2.1
T-Bar	200mm (6) x 200mm (8)	2.4	2.7	3.0	3.3	3.6	3.9	
T-Bar	200mm (6) x 200mm (10)	4.2	4.5	4.8	5.1	5.4	5.7	



**BUILDERS
STEEL DIRECT**

Builders Steel Direct Pty. Ltd.

27 Vallance Street
 St Marys NSW 2760

P: 02 9623 8584

F: 02 8458 0729



sales@builderssteeldirect.com.au