



Manufactured from Colorbond




Think strength... think COLORBOND® steel

Leading scientists have been testing COLORBOND® steel for over 50 years in some of our country's harshest climate conditions. So you have the peace of mind of knowing COLORBOND® steel is made and tested for Australia and backed by a warranty* from BlueScope Steel, one of Australia's largest companies.

If it's not BRANDED it's not



Not all coloured steel fencing is made from COLORBOND® steel. Be sure to get what you pay for. Fencing made from COLORBOND® steel is branded with a subtle laser engraving (on either side of the fence) at least three times on each 2.4 metre fencing section.



If you can't find the branding then the panels are not genuine COLORBOND® steel.





REFLECT™ (same both sides)











Whether your primary concern is security, making an aesthetic addition to your property or you want to erect the very best boundary fencing to divide you and your neighbour's property - insist on ColorMAX® Boundary Fencing manufactured from COLORBOND®.

Available in two profiles ColorMAX® REFLECT™ (same both sides) or ColorMAX® ORIGINAL. 23 designer colours. Option of LouvrLAT® (5 louvres), SlatLAT™ (4 slats), pressed 3D Lattice, plastic post caps & decorative metal ball caps.

ColorMAX® Boundary Fencing meets Australian Standards AS1397, AS2728, AS4040.2 and AS/NZS1170 when installed to manufacturer specifications and has a wind gust loading of 216km/h.

*Backed by the strength of a 10 year BlueScope Steel Warranty.





Manufactured from Colerbond

Easy To Maintain. We understand you want to choose a fence that is easy to maintain, so you' re free to enjoy your weekends. Fifty years of innovation in Colorbond® steel ensures that there's no need to be spending your time painting, oiling or replacing palings. To ensure the maximum life and appearance from your Colorbond® steel fence, we recommend you simply hose it down, removing any debris, at least every 6 months. It's that easy.

- · Avoid earth or soil coming in contact with the fence
- · Check drainage holes occasionally for any blockages.
- Fertilisers & garden chemicals should not be used in or around fences to limit contact.
- · Slope all concrete away from posts to limit any water build up around the base of posts.
- · Metalling from self drilling screws, rivet shanks and other steel particles will cause rust staining. Remove from fencing immediately following installation.