# The importance of choosing the right product



Lohas Australia Pty Ltd

ABN 25 138 686 549

www.lohasau.com | info@lohasau.com

# **CLIMATE ZONES ADVERSE**

Sea and mountains. Snow and burning sun. Constructions located in an extreme weather condition is recommended to use tiles with low water absorption and high frost resistance.






# REHABILITATION



Moisture problems, cracks, and damage over time needs to be recovered to the perfect condition. It is advisable to use products with high flexural strength to facilitate the work of installation and assembly





to use dimensional symmetry products





# TRADITIONAL BUILDINGS

The construction of traditional architecture needs to have highly durable products with quick and easy installation as it stays for generations.





**Premium Spanish Roof Tiles** 













# Onda

Length x width: 457 x 289 mm Unit / m2: 10.5 Weight per unit: 4.00 Kg

Media Teja de Teja







Final de lateral lateral Caballete Limatesa derecho izquierdo

























Pieza tana





Tanon do

Teja de
















































# Marselha

Length x width: 455 x 263 mm Units / m2: 11.5 Weight x unit: 3.60 Kg







Caballete a

4 aguas

# Accessories



Teja de

alero



Media

teia



doble




ventilacion











#### Wakaflex

WAKAFLEX is a very strong waterproof adhesive band: Suitable for sealing between tiles and walls, fireplaces. pillars, etc. Does not suffer from anyrise in the wind, water, sun and inclement weather



### Figaroll Plus

Figaroll Plus is an optimal ridge and hip roll with double ventilation channel system. Stretchability up to 50%. Ideal for aeration and resistance against rain or snow



### Figaroll Universal Roll Fix

Figaroll Universal Roll-Fix is the perfect finish for ventilated ridge and hip lines. suitable for any tile profile. Quick and easy installation



# Cobert Film (270 gr & 135 gr)

A polypropylene multilayer film. Waterproofing under the tile space: Protecting from dust and snow penetration. Prevents condensation



### Film Bajo Teja Permo Ultra SK

A polypropylene multilayer film. Waterproofing under tile space; Protecting from dust and snow penetration. Prevents condensation. High impermeability with maximum safety



#### Film Ecovent

A polypropylene multilayer film. Waterproofing under tile space; protecting from dust and snow penetration. Prevents condensation.



#### Rastrel De Alero Liso

Synthetic Rastrel comb, comprising a rigid bottom and upper flexible tines for positive fit any tile profile.



#### Rastrel Metalico

Rastrel galvanized sheet metal, used to support both on slabs tiles, boards, and on board under tile.



#### Soporte Metalico De Caballete

Element aluminum for perfect alignment ridge battens and limatesa brackets.



#### Ganchos De Cumbrera

Lacquered aluminum parts, ideal for workholding ridge.



## Metal Profile

Omega metal profiles, "U" and "C" Material: Galvanized steel



#### Pinaculo

Range of Colours: Red, Flamed red, Old Castile, Flamed straw

## Totems



Eagle













